


ARK


by KD Lab




USE



LED



FEATURES




DESCRIPTION

Wall lamp for architectural effects. Structure in extruded aluminium alloy 6060/T6. Die-cast aluminium details. Polyester powder coating and phosphate treatment to increase corrosion resistance. Diffuser made of opal polycarbonate, specific for Led, which combines maximum brightness with the ability to avoid the spot effect of Led. MIX version is equipped with 5° emission diffuser made of transparent polycarbonate to ensure the best brightness. AISI 316 stainless steel screws. Silicone gasket suitable to withstand very high temperatures. Equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Laser-cut metal dissipating plate. All electronic ballasts are equipped with thermal and short-circuit protection, against overloading and mains voltage.

SETTLEMENT CODE

Complete the code by entering the number corresponding to the desired color in the space provided


STANDARD COLORS



RAL 9016 - Embossed white: **1**
RAL 9007 - Embossed grey: **6**
RAL 9005 - Embossed black: **7**
Rust: **8**

other colors on request


ARK 10



IP65	TYPE	POWER	FLUX ¹
	LED	8W	950lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
	L003 <input type="text"/> .W	L003 <input type="text"/> .N


ARK 10-2



IP65	TYPE	POWER	FLUX ¹
	LED	16W	1900lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
	L004 <input type="text"/> .W	L004 <input type="text"/> .N

ARK 10 MIX



IP65	TYPE	POWER	FLUX ¹
	LED	14W	1450lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
	L005 <input type="text"/> .W	L005 <input type="text"/> .N

Brightest LED versions on request

Other version on request

¹ Nominal luminous flux