


# KIT 2

by KD Lab




## USE



## LED



## FEATURES




## DESCRIPTION

Wall lamp for diffused lighting. Structure in extruded aluminium alloy 6060/T6. Die-cast aluminium details. Polyester powder coating and phosphate treatment to increase corrosion resistance. Opal polycarbonate diffuser, specific for Led, which combines maximum brightness with the ability to avoid the dot effect of Led. AISI 316 stainless steel screws. Silicone gasket suitable to withstand very high temperatures. Equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Laser-cut metal dissipating plate. Built-in electronic ballast. All electronic ballasts are equipped with thermal and short-circuit protection, protection against overvoltage and overloading.

SETTLEMENT CODE

Complete the code by entering the number corresponding to the desired color in the space provided


STANDARD COLORS



RAL 9016 - Embossed white: **1**  
RAL 9007 - Embossed grey: **6**  
RAL 9005 - Embossed black: **7**  
Rust: **8**

other colors on request

KIT 2



IP65	TYPE	POWER	FLUX <sup>1</sup>
	E27	1x12W*	1x1320lm*
	LED	11W	1700lm

CODE		
	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L082 <input type="text"/> .IN	L082 <input type="text"/> .W	L082 <input type="text"/> .N

Brightest LED versions on request