

NANO




by KD Lab



USE

LED

FEATURES



DESCRIPTION

Bollard for diffused light. Structure in extruded aluminium alloy 6060/T6. Polycarbonate details. Polyester powder coating and phosphate treatment to increase corrosion resistance. Small opal polycarbonate diffuser specifically designed for Led, combining maximum brightness with the ability to avoid the spot effect of Led. Internal conical aluminium reflector to direct the light at 360° without any shadow zones. AISI 316 stainless steel screws. Rubber gasket. Equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Laser-cut metal dissipating plate. Built-in electronic ballast. All electronic ballasts are equipped with thermal and short-circuit protection, protection against overvoltage and overloading. Supplied with a watertight electrical connection device.

SETTLEMENT CODE

Complete the code by entering the number corresponding to the desired color in the space provided


STANDARD COLORS



RAL 9007 - Embossed grey: **6**
RAL 9005 - Embossed black: **7**
Rust: **8**

other colors on request

NANO 12




IP65

TYPE

POWER

FLUX¹



shadowless

LED

5W

800lm

CODE




CCT 3000°K
CRI > 90

CCT 4000°K
CRI > 90

L096 .W

L096 .N

NANO 35




IP65

TYPE

POWER

FLUX¹



shadowless

LED

5W

800lm



CCT 3000°K
CRI > 90


CCT 4000°K
CRI > 90

L097 .W

L097 .N

Brightest LED versions on request

Other version on request



¹ Nominal luminous flux

NANO




by KD Lab



USE

LED

FEATURES



DESCRIPTION

Wall or ceiling lamp for diffused light. Structure in extruded aluminium alloy 6060/T6. Polycarbonate details. Polyester powder coating and phosphate treatment to increase corrosion resistance. Small opal polycarbonate diffuser specifically designed for Led, combining maximum brightness with the ability to avoid the spot effect of Led. Internal conical aluminium reflector to direct the light at 360° without any shadow zones. AISI 316 stainless steel screws. Rubber gasket. Equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Laser-cut metal dissipating plate. Built-in electronic ballast. All electronic ballasts are equipped with thermal and short-circuit protection, protection against overvoltage and overloading. Supplied with a watertight electrical connection device.

SETTLEMENT CODE


Complete the code by entering the number corresponding to the desired color in the space provided

STANDARD COLORS



other colors on request

NANO-APS



IP65



TYPE

LED

POWER

5W

FLUX¹

800lm

CODE



CCT 3000°K
CRI>90

CCT 4000°K
CRI>90

L098 .W

L098 .N

Brightest LED versions on request