

# PLAZA

by KD Lab





## USE

## LED



## FEATURES



## DESCRIPTION

Bollard for direct lighting. Post and structure in extruded aluminium alloy 6060/T6. Die-cast aluminium details. Polyester powder coating and phosphate treatment to increase corrosion resistance. Diffuser made of opal polycarbonate, specific for Led, which combines maximum brightness with the ability to avoid the spot effect of Led. AISI 316 stainless steel screws. Silicone gasket suitable to withstand very high temperatures. Led version equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Laser-cut metal dissipating plate. Built-in electronic ballast. All electronic ballasts are equipped with thermal and short-circuit protection, protection against overvoltage and overloading. Supplied with a watertight electrical connection device.

**SETTLEMENT CODE**


Complete the code by entering the number corresponding to the desired color in the space provided


**STANDARD COLORS**


	RAL 9007 - Embossed grey: <b>6</b>
	RAL 9005 - Embossed black: <b>7</b>
	Rust: <b>8</b>

other colors on request


**PLAZA 90**





IP65	TYPE	POWER	FLUX <sup>1</sup>
	E27	1x12W*	1x1320lm*
	LED	23W	3120lm

CODE		
	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L119 <input type="checkbox"/> .IN		
	L119 <input type="checkbox"/> .W	L119 <input type="checkbox"/> .N

**PLAZA 180**



IP65	TYPE	POWER	FLUX <sup>1</sup>
	E27	1x12W*	1x1320lm*
	LED	23W	3120lm


CODE		
	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L121 <input type="checkbox"/> .IN		
	L121 <input type="checkbox"/> .W	L121 <input type="checkbox"/> .N

Complies with UNI 10819 on the limitation of the dispersion upwards of the luminous flux.

Brightest LED versions on request

Other version on request

\*Suggested value - light source not supplied



<sup>1</sup>Nominal luminous flux

**SETTLEMENT CODE**

Complete the code by entering the number corresponding to the desired color in the space provided


**STANDARD COLORS**



RAL 9007 - Embossed grey: **6**  
RAL 9005 - Embossed black: **7**  
Rust: **8**

other colors on request


**PLAZA 92**



IP65	TYPE	POWER	FLUX <sup>1</sup>
	E27	2x12W*	2x1320lm*
	LED	46W	6240lm

CODE		
	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L120 <input type="checkbox"/> .IN		
	L120 <input type="checkbox"/> .W	L120 <input type="checkbox"/> .N

**PLAZA 182**



IP65	TYPE	POWER	FLUX <sup>1</sup>
	E27	2x12W*	2x1320lm*
	LED	46W	6240lm


CODE		
	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L122 <input type="checkbox"/> .IN		
	L122 <input type="checkbox"/> .W	L122 <input type="checkbox"/> .N

Complies with UNI 10819 on the limitation of the dispersion upwards of the luminous flux.

Brightest LED versions on request

Other version on request

\*Suggested value - light source not supplied



<sup>1</sup>Nominal luminous flux