


STILO/C


by 6366 DownTown




USE



LED



FEATURES



DESCRIPTION

Suspension lamp for diffused lighting. Injection-molded opal acrylic diffuser with semi-gloss finish. Painted or galvanized metal structure. Painted polycarbonate top cover matching the color of the structure. Steel support cable, white or transparent PVC covered power cord. Led version equipped with SMD Led circuit with high color rendering index (CRI90) and high-energy efficiency. Printed metal dissipating plate. Built-in electronic ballast. DM version equipped with dimmable ballast with DALI/PUSH interface. All electronic ballasts are equipped with thermal and short-circuit protection, against mains overvoltage and overloading.

SETTLEMENT CODE

Complete the code by entering the number corresponding to the desired color in the space provided


STANDARD COLORS



RAL 9016 - Matt white: **1**
Chrome finish: **0**
Satin gold color: **2**
Satin copper color: **3**

other colors on request


STILO/C 400



IP20	TYPE	POWER	FLUX ¹
	E27	1x19W*	1x2400lm*
	LED	20W	3000lm
	LED DM	20W	3000lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L158 <input type="text"/> .IN		
	L158 <input type="text"/> .W	L158 <input type="text"/> .N
	L158 <input type="text"/> .WD	L158 <input type="text"/> .ND


STILO/C 500



IP20	TYPE	POWER	FLUX ¹
	E27	1x19W*	1x2400lm*
	LED	40W	5800lm
	LED DM	40W	5800lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L159 <input type="text"/> .IN		
	L159 <input type="text"/> .W	L159 <input type="text"/> .N
	L159 <input type="text"/> .WD	L159 <input type="text"/> .ND

STILO/C 600



IP20	TYPE	POWER	FLUX ¹
	E27	1x19W*	1x2400lm*
	LED	40W	5800lm
	LED DM	40W	5800lm

CODE	CCT 3000°K CRI>90	CCT 4000°K CRI>90
L160 <input type="text"/> .IN		
	L160 <input type="text"/> .W	L160 <input type="text"/> .N
	L160 <input type="text"/> .WD	L160 <input type="text"/> .ND

Brightest LED versions on request

Other version on request

*Suggested value - light source not supplied


¹Nominal luminous flux
LED DM: dimmable DALI - PUSH

STILO/C


by 6366 DownTown




USE



LED



FEATURES



DESCRIPTION

System for the installation of multiple suspensions consisting of several lighting points. This structure allows free and independent installation of each light point, where the layout and length of the cable can be adjusted as desired. It requires only one ceiling supply point and is easy to install. The suspensions installed with this system must be purchased separately, in addition to the kit, and are wired with 3 meters of cable.

STANDARD COLORS




RAL 9016 - Matt white

other colors on request

KIT GRAPPOLO 2

IP20

CODE



max 2 fittings (see page 193)


L0851.G2

Grappolo kit is composed by:
- 1 top cover Ø160mm made in white painted metal.
- fixing system made in white painted metal for each suspension.
Suspensions must be purchased in addition to the kit and they are equipped with 3mt wires long.
By request we can provide suspensions with longer cables.

KIT GRAPPOLO 3

IP20

L0851.G3




max 3 fittings (see page193)

Grappolo kit is composed by:
- 1 top cover Ø160mm made in white painted metal.
- fixing system made in white painted metal for each suspension.
Suspensions must be purchased in addition to the kit and they are equipped with 3mt wires long.
By request we can provide suspensions with longer cables.

KIT GRAPPOLO 4

IP20

L0851.G4



max 4 fittings (see page193)

Grappolo kit is composed by:
- 1 top cover Ø160mm made in white painted metal.
- fixing system made in white painted metal for each suspension.
Suspensions must be purchased in addition to the kit and they are equipped with 3mt wires long.
By request we can provide suspensions with longer cables.

Other version on request

*Suggested value - light source not supplied

¹Nominal luminous flux
LED DM: dimmable DALI - PUSH